

**IN THE CLAIMS**

1. (Original): A system for displaying caller information, comprising:  
a caller terminal for storing caller information and transmitting data including the caller information during a call;  
a service system for receiving the data including the caller information from the caller terminal and transmitting the data to a receiver terminal; and  
the receiver terminal for receiving the data from the service system, storing the caller information to be linked with a telephone number on the caller terminal, and displaying the caller information when a paging signal is received.

2. (Original): The system as recited in claim 1, wherein the caller information is automatically stored in the receiver terminal by linking a telephone number contained in the data with a telephone number stored in a telephone directory.

3. (Currently Amended): A system for displaying caller information, comprising:  
a caller terminal for transmitting data including caller information and a phone number of a designated ~~designed~~ receiver terminal during a call;  
a service system for temporarily storing the data received from the caller terminal and transmitting the data to the designated ~~designed~~ receiver terminal when the designated ~~designed~~ receiver terminal is in a state for receiving ~~that~~ the caller information ~~can be received~~; and  
the designated receiver terminal for receiving the data from the service system, storing the caller information to be linked with a phone number of the caller terminal, and displaying the caller information when a paging signal is received.

4. (Currently Amended): The system as recited in claim 32, wherein the caller information is automatically stored in the designated receiver terminal by linking a telephone number contained in the data with a telephone number stored in a telephone directory.

5. (Currently Amended): A system for displaying caller information, comprising:

a caller terminal;

a service system for storing data including the caller information and phone numbers of designated receiver terminals and transmitting the caller information to the designated receiver terminal when the designated receiver terminal is in a state ~~that can receive~~ for receiving the caller information; and

the designated receiver terminal for receiving the data from the service system, storing the caller information to be linked with a phone number of the caller terminal, and displaying the caller information when a paging signal is received.

6. (Currently Amended): The system as recited in claim 5, wherein the caller information is automatically stored in the designated receiver terminal by linking a telephone number contained in the data with a telephone number stored in a telephone directory.

7. (Original): The system as recited in claim 5, wherein the data including the caller information is stored in the service system via a wireless Internet or a personal computer.

8. (Currently Amended): A method for displaying caller information, comprising ~~the steps of~~:

(a)——at a caller terminal, storing caller information and transmitting data including the caller information to a service system during a call;

(b)——at the receiver terminal, receiving the data from the service system to store the caller information to be linked with a phone number of the caller terminal; and

(e)——at the receiver terminal, displaying the caller information when a paging signal is received.

9. (Original): The method as recited in claim 8, wherein the caller information is automatically stored in the receiver terminal by linking a telephone number contained in the data with a telephone number stored in a telephone

directory.

10. (Currently Amended): A method for displaying caller information, comprising ~~the steps of~~:

(a) ~~at a caller terminal, transmitting data packets including the caller information and a phone number of a designated receiver terminal to a service system;~~

(b) ~~at a service system, temporarily storing the data from the caller terminal and transmitting the data to the designated receiver terminal when the designated receiver terminal is in a state that can receive for receiving the caller information;~~

(c) ~~at the designated receiver terminal, receiving the data from the service system to store the caller information to be linked with a phone number of the caller terminal; and~~

(d) ~~at the designated receiver terminal, displaying the caller information when a paging signal is received.~~

11. (Currently Amended): The method as recited in claim 10, wherein the caller information is automatically stored in the designated receiver terminal by linking a telephone number contained in the data with a telephone number stored in a telephone directory.

12. (Currently Amended): A method for displaying caller information, comprising ~~the steps of~~:

(a) ~~at a service system, storing data including the caller information and a phone number of a designated receiver terminal and transmitting the caller information to the designated receiver terminal when the designated receiver terminal is in a state that can receive for receiving the caller information;~~

(b) ~~at the designated receiver terminal, receiving the data from the service system to store the caller information to be linked with a phone number of the designated receiver terminal; and~~

(c) ~~at the designated receiver terminal, displaying the caller information when a paging signal is received.~~

13. (Currently Amended): The system as recited in claim 12, wherein the caller information is automatically stored in the designated receiver terminal by linking a telephone number contained in the data with a telephone number stored in a telephone directory.

14. (Original): The method as recited in claim 12, wherein the data including the caller information is stored in the service system via a wireless Internet or personal computer.

15. (Currently Amended): A mobile terminal, comprising:  
a radio frequency (RF) receiver for receiving data including caller information during a call;

a memory unit for storing the caller information to be linked with a telephone number of a caller terminal; and

a controller for controlling a mobile terminal to display the caller information when a paging signal is received.

16. (Original): The mobile terminal as recited in claim 15, wherein the caller information is automatically stored in the receiver terminal by linking a telephone number contained in the data with a telephone number stored in a telephone directory.

17. (New): A mobile terminal, comprising:  
a memory unit for storing caller information; and  
a radio frequency transmitter for transmitting data including the caller information during a call.

18. (New): The mobile terminal of claim 17, wherein the data includes the caller information and a telephone number of a receiving party.